

Package: loc (via r-universe)

October 10, 2024

Type Package

Title What the Package Does (Title Case)

Version 0.1.0

Author Who wrote it

Maintainer The package maintainer <yourself@somewhere.net>

Description More about what it does (maybe more than one line) Use four spaces when indenting paragraphs within the Description.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Config/rextendr/version 0.3.1

Suggests tinytest

RoxygenNote 7.3.1

Roxygen list(markdown = TRUE)

URL <https://github.com/etiennebacher/loc>

BugReports <https://github.com/etiennebacher/loc/issues>

Repository <https://etiennebacher.r-universe.dev>

RemoteUrl <https://github.com/etiennebacher/loc>

RemoteRef v0.0.1

RemoteSha c7a9739bfd9fad3b456870ee16b13c1514f658c1

Contents

loc-package	2
count_loc	2

Index	4
--------------	----------

loc-package	<i>loc: What the Package Does (Title Case)</i>
-------------	--

Description

More about what it does (maybe more than one line) Use four spaces when indenting paragraphs within the Description.

See Also

Useful links:

- <https://github.com/etiennebacher/loc>
- Report bugs at <https://github.com/etiennebacher/loc/issues>

count_loc	<i>Count lines of code</i>
-----------	----------------------------

Description

Count lines of code

Usage

```
count_loc(
  paths = ".",
  excluded = NULL,
  include_hidden = FALSE,
  languages = "R"
)
```

Arguments

paths	Paths to include.
excluded	Paths to exclude.
include_hidden	Count hidden files and directories? Default is FALSE.
languages	Languages to consider. See the list here: https://github.com/XAMPPRocky/tokei?tab=readme-ov-file#supported-languages .

Value

A data.frame with 4 columns: number of blank lines, comments, code, and whether the count is accurate.

Examples

```
tmp <- tempfile(fileext = ".R")
cat("
library(loc)
# This is a wrong function
foo <- function(x) {
  x + 1
}

", file = tmp)
count_loc(tmp)
```

Index

`count_loc`, [2](#)

`loc (loc-package)`, [2](#)

`loc-package`, [2](#)